


Braga 45° Geberit PP-HTs



Figura di esempio



Dati tecnici

Materiale	PP
-----------	----

Dilatazione termica	0.12 mm/(m·K)
Conduttività termica tubo	0.22 W/(m·K)
Densità	950 kg/m³

No. art.	Colore / superficie	d, Ø	d1, Ø	arc	L	Z1	Z2	Z3
391.201.00.2	Giallo traffico B	50 mm	40 mm	45 °	11.6 cm	0.5 cm	5.6 cm	5.4 cm
391.203.00.2	Giallo traffico B	110 mm	40 mm	45 °	12.7 cm	3.7 cm	9.8 cm	9.4 cm
391.212.00.2	Giallo traffico B	75 mm	50 mm	45 °	13.4 cm	-0.1 cm	7.9 cm	7.4 cm
391.213.00.2	Giallo traffico B	110 mm	50 mm	45 °	14.8 cm	-1.7 cm	10.4 cm	9.1 cm
391.218.00.2	Giallo traffico B	90 mm	50 mm	45 °	12.7 cm	-0.9 cm	9 cm	8.2 cm
391.223.00.2	Giallo traffico B	110 mm	75 mm	45 °	17.5 cm	0 cm	11.6 cm	10.9 cm
391.228.00.2	Giallo traffico B	90 mm	75 mm	45 °	16.3 cm	0.9 cm	10.3 cm	10 cm
391.234.00.2	Giallo traffico B	125 mm	110 mm	45 °	22.6 cm	2.2 cm	13.8 cm	14.1 cm
391.235.00.2	Giallo traffico B	160 mm	110 mm	45 °	23.4 cm	0 cm	16.5 cm	15.8 cm
391.290.00.2	Giallo traffico B	32 mm	32 mm	45 °	4.4 cm	0.9 cm	4 cm	4 cm
391.200.00.2	Giallo traffico B	40 mm	40 mm	45 °	11.5 cm	1 cm	4.9 cm	4.9 cm
391.211.00.2	Giallo traffico B	50 mm	50 mm	45 °	13 cm	1.2 cm	6.1 cm	6.1 cm
391.222.00.2	Giallo traffico B	75 mm	75 mm	45 °	16.8 cm	1.7 cm	9.1 cm	9.1 cm
391.288.00.2	Giallo traffico B	90 mm	90 mm	45 °	11 cm	2 cm	11 cm	11 cm
391.233.00.2	Giallo traffico B	110 mm	110 mm	45 °	22.6 cm	2.5 cm	13.3 cm	13.3 cm
391.244.00.2	Giallo traffico B	125 mm	125 mm	45 °	26.6 cm	2.8 cm	15.2 cm	15.2 cm
391.255.00.2	Giallo traffico B	160 mm	160 mm	45 °	38 cm	3.6 cm	19.4 cm	31.3 cm