


# RACCORDI PER TERMOFUSIONE • TERMOFUSION FITTINGS




## CURVA A 45°

Materiale: PP-R fino al ø63. Dal ø75 PP-RCT  
 Norme: DIN 16962 - UNI EN ISO 15874  
 Gamma: ø16÷125mm

## 45° ELBOW

Material: PP-R until ø63. From ø75 PP-RCT  
 Standards: DIN 16962 - UNI EN ISO 15874  
 Range: ø16 ÷ 125mm

| Codice<br>Item Code | Ø   | Pack | kg/p  | Volume<br>m³/p | Dn  | D1   | D     | L1   | H1   | H     |
|---------------------|-----|------|-------|----------------|-----|------|-------|------|------|-------|
| 03NC4516            | 16  | 150  | 0,011 | 0,0007         | 16  | 15   | 25    | 13   | 16,5 | 37    |
| 03NC4520            | 20  | 200  | 0,017 | 0,0009         | 20  | 16,5 | 29    | 16   | 21,5 | 46    |
| 03NC4525            | 25  | 150  | 0,022 | 0,0001         | 25  | 23,5 | 34    | 16   | 24,5 | 53,5  |
| 03NC4532            | 32  | 40   | 0,037 | 0,0002         | 32  | 30   | 42    | 20   | 29   | 64    |
| 03NC4540            | 40  | 30   | 0,071 | 0,0003         | 40  | 36   | 53    | 22   | 32   | 72,5  |
| 03NC4550            | 50  | 30   | 0,116 | 0,0006         | 50  | 47,5 | 66    | 25   | 39,5 | 90    |
| 03NC4563            | 63  | 35   | 0,205 | 0,0010         | 63  | 60   | 83    | 29   | 45   | 105   |
| 03NC4575            | 75  | 16   | 0,428 | 0,0022         | 75  | 70   | 99    | 33   | 65   | 145   |
| 03NC4590            | 90  | 12   | 0,324 | 0,0030         | 90  | 86   | 123,5 | 37   | 57   | 140   |
| 03NC45110           | 110 | 6    | 1,030 | 0,0060         | 110 | 100  | 146   | 43   | 70   | 169,5 |
| 03NC45125           | 125 | 4    | 1,350 | 0,0090         | 125 | 113  | 165   | 47,5 | 78   | 189,5 |



## CURVA A 45° MASCHIO/FEMMINA

Materiale: PP-R  
 Norme: DIN 16962 - UNI EN ISO 15874  
 Gamma: ø20÷32mm

## MALE/FEMALE 45° ELBOW

Material: PP-R  
 Standards: DIN 16962 - UNI EN ISO 15874  
 Range: ø20÷32mm

| Vecchio Codice<br>Old Item Code | Nuovo Codice<br>New Item Code | Ø  | Pack | kg/p  | Volume<br>m³/p | Dn1 | Dn2 | D1   | D    | L1   | L2 | H1   |
|---------------------------------|-------------------------------|----|------|-------|----------------|-----|-----|------|------|------|----|------|
| 03NCMF4520                      | 03NC4520MF                    | 20 | 100  | 0,016 | 0,0001         | 20  | 20  | 30,5 | 30,5 | 14,5 | 15 | 19,5 |
| 03NCMF4525                      | 03NC4525MF                    | 25 | 70   | 0,028 | 0,0002         | 25  | 25  | 34,5 | 34,5 | 16   | 16 | 22   |
| 03NCMF4532                      | 03NC4532MF                    | 32 | 1    | -     | -              | 32  | 32  | 43   | 43   | 20   | 17 | 26   |