


RACCORDI DI TRANSIZIONE • TRANSITION FITTINGS



GOMITO A 90° FILETTATO MASCHIO

Materiale: PP-R - Ottone

Norme: DIN 16962 - UNI EN ISO 15874

Gamma: $\varnothing 16 \times \frac{1}{2}'' \div 32 \times 1''$ mm

Note: Filettatura ISO

MALE THREADED 90° ELBOW


Material: PP-R - Brass

Standards: DIN 16962 - UNI EN ISO 15874

Range: $\varnothing 16 \times \frac{1}{2}'' \div 32 \times 1''$ mm

Notes: ISO Threaded

Vecchio Codice Old Item Code	Nuovo Codice New Item Code	Ø	Pack	kg/p	Volume m³/p	Dn	D1	D	F	LF min	L1	L2	L	H1	H
03NGM1612	03NC901612SCML	16 x ½"	50	0,109	0,0002	16	14	37	½"	13,2	13	54	68,5	27,5	46
03NGM2012	03NC902012SCML	20 x ½"	60	0,108	0,0002	20	14	37	½"	13,2	16	54	68,5	27,5	46
03NGM2512	03NC902512SCML	25 x ½"	50	0,116	0,0002	25	14	37	½"	13,2	17	54	71,5	30,5	49
03NGM2534	03NC902534SCML	25 x ¾"	40	0,154	0,0002	25	18,5	42	¾"	14,5	17	54	73,5	30,5	51,5
03NGM3212	03NC903212SCML	32 x ½"	30	0,136	0,0003	32	14	42	½"	13,2	18	61	82	36	57
03NGM3234	03NC903234SCML	32 x ¾"	30	0,180	0,0003	32	18,5	42	¾"	14,5	18	61	84	36	57
03NGM321	03NC90321SCML	32 x 1"	25	0,300	0,0004	32	24	54	1"	16,8	20	65	86,5	47	74



GOMITO A 90° FILETTATO FEMMINA CON STAFFA

Materiale: PP-R - Ottone

Norme: DIN 16962 - UNI EN ISO 15874

Gamma: $\varnothing 16 \times \frac{1}{2}'' \div 20 \times \frac{1}{2}''$ mm

Note: Filettatura ISO

FEMALE THREADED 90° ELBOW WITH HANGER

Material: PP-R - Brass

Standards: DIN 16962 - UNI EN ISO 15874

Range: $\varnothing 16 \times \frac{1}{2}'' \div 20 \times \frac{1}{2}''$ mm

Notes: ISO Threaded

Vecchio Codice Old Item Code	Nuovo Codice New Item Code	Ø	Pack	kg/p	Volume m³/p	Dn	D1	D2	D	F	LF min	L1	L2	L	H1	H2	H
03NTER1612	03NCT1901612SCFL	16 x ½"	40	0,084	0,0002	16	14	3	37	½"	11,5	13	39	53,5	27,5	57	63,5
03NTER2012	03NCT1902012SCFL	20 x ½"	40	0,083	0,0002	20	14	3	37	½"	11,5	16	39	53,5	27,5	57	63,5