


RACCORDI PER TERMOFUSIONE • TERMOFUSION FITTINGS




GOMITO 90° MASCHIO/FEMMINA

Materiale: PP-R
Norme: DIN 16962 - UNI EN ISO 15874
Gamma: $\varnothing 20 \div 40$ mm

MALE/FEMALE 90° ELBOW

Material: PP-R
Standards: DIN 16962 - UNI EN ISO 15874
Range: $\varnothing 20 \div 40$ mm

Vecchio Codice <i>Old Item Code</i>	Nuovo Codice <i>New Item Code</i>	Ø	Pack	kg/p	Volume m³/p	Dn1	Dn2	D1	D	L1	L2	L	H1	H
03NGMF20	03NC9020MF	20	100	0,015	0,0001	20	20	13,2	30	16	29	39	28,5	43,5
03NGMF25	03NC9025MF	25	60	0,025	0,0001	25	25	16,6	35	16	33	45,5	35	52,5
03NGMF32	03NC9032MF	32	30	0,058	0,0004	32	32	24	43	20	34	50	47,5	68,5
03NGMF40	03NC9040MF	40	20	0,098	0,0054	40	40	33	52	21	44,5	66	54,5	80,4



CURVA A 3 VIE

Materiale: PP-R
Norme: DIN 16962 - UNI EN ISO 15874
Gamma: $\varnothing 20$ mm

ELBOW THREE OUTLETS

Material: PP-R
Standards: DIN 16962 - UNI EN ISO 15874
Range: $\varnothing 20$ mm

Codice <i>Item Code</i>	Ø	Pack	kg/p	Volume m³/p	Dn	D1	D	L1	L2	L	H1	H
03NCTV20	20	150	0,021	0,0001	20	18	28	15	26	40	26	40